Continental
The Future in Motion

Fuel Line / PCV / Emission Control Hose SAE J30R7



Application
A multipurpose fuel hose that can be used as a fuel line, PCV connection, emission control line or fuel return line.

Specific Fuel
Unleaded gasoline, diesel fuel, gasoline blends of ethanol (E-10), E85 and sour gas.

Construction
Tube: Black Nitrile
Reinforcement: 2-spiral synthetic
Cover: Black Chlorinated Polyethylene (CPE)
Length: See table below. 1.6' (clamshell), 2' (clamshell), 25' (spool), 50' (carton), 250' (reel)

Specifications
Temperature Range: -40°F to 257°F (-40°C to 125°C)
SAE Specifications: SAE J30R7
Product Specifications: 580019
Branding: Continental ID WP Fuel/Emission SAE 30R7, Made in U.S.A.
Installation: See selection of Continental connectors and clamps

Warning: Do not use for pressure lines on fuel-injected engines.

Part #	ID (in.)	OD (in.)	Length (ft.)	Working Pressure (psi)	Burst Pressure (psi)	Weight (lbs./ft.)
65132	1/8	0.34	50	50	250	0.05
65136	3/16	0.41	2	50	250	0.06
65125	3/16	0.41	25	50	250	0.06
65122	1/4	0.50	2	50	250	0.09
65126	1/4	0.50	25	50	250	0.09
65154	1/4	0.50	250	50	250	0.09
65123	5/16	0.56	2	50	250	0.11
65127	5/16	0.56	25	50	250	0.11
65155	5/16	0.56	250	50	250	0.11
65119	11/32	0.59	1.6	50	250	0.11
65185	11/32	0.59	50	50	250	0.11
65124	3/8	0.63	2	50	250	0.12
65128	3/8	0.63	25	50	250	0.12

Part #	ID (in.)	OD (in.)	Length (ft.)	Working Pressure (psi)	Burst Pressure (psi)	Weight (lbs./ft.)
65156	3/8	0.63	250	50	250	0.12
65140	7/16	0.71	2	35	175	0.16
65129	7/16	0.71	25	35	175	0.16
65157	7/16	0.71	250	35	175	0.16
65120	15/32	0.75	1.6	35	175	0.17
65186	15/32	0.75	50	35	175	0.17
65116	1/2	0.78	50	35	175	0.18
65158	1/2	0.78	250	35	175	0.18
65121	19/32	0.91	1.6	35	175	0.24
65187	19/32	0.91	50	35	175	0.24
65117	5/8	0.94	50	35	175	0.24
65118	3/4	1.13	50	35	175	0.42

ELITE
Premium heavy-duty aftermarket products

Legal Notice
The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates.
Copyright © 2015 ContiTech AG. All rights reserved.