

LOCTITE® LB 8632

Known as LOCTITE® ViperLube® Clear High Performance Synthetic Grease
January 2015

PRODUCT DESCRIPTION

LOCTITE® LB 8632 provides the following product characteristics:

Technology	Oil & Grease
Appearance	Opaque white ^{LMS}
Cure	Non-curing
Application	Lubrication

LOCTITE® LB 8632 is an advanced multi-purpose NLGI Grade 2 grease that is composed of synthetic PAO (polyalphaolefin) base stocks and a fumed silica thickener. Due to its base oil chemistry this product is ideal for use on food processing equipment as a lubricant for machine parts and equipment, as a release agent on gaskets or seals, and is an acceptable choice for use as a protective anti-rust film. LOCTITE® LB 8632 also contains PTFE filler which when compared to other food grade lubricants provides excellent wear resistance under extreme loads. It is an excellent lubricant for industrial processes where a wide range of operating temperatures and environments are encountered.

NSF International

Registered to NSF Category H1 for use as a lubricant with incidental food contact in and around food processing areas. **Note:** This is a regional approval. Please contact your local Technical Service Center for more information and clarification

TYPICAL PROPERTIES

Specific Gravity @ 25 °C	0.9 to 0.93 ^{LMS}
Penetration, ISO 2137, 1/10 mm	265 to 295 ^{LMS}
Viscosity, base oil, ASTM D445, cSt:	
@ 40 °C	103
@ 100 °C	12
Drop Point, ISO 2176, °C	≥300 ^{LMS}
Low-Temperature Torque, -40 °C, ASTM D1478, N·m:	
Start	0.42
1 Hour Running	0.14
Oil Separation, ASTM D6184, % wt. loss:	
30 hours @ 100 °C	≤4 ^{LMS}
Oil Separation in Storage, ASTM D1742, % wt. loss	3.1
Copper Corrosion, ISO 2160	1b
Wear Protection, Scar Diameter, ASTM D2266, mm	0.6
Fretting Wear, ASTM D4170, mg	0.8
EP Performance, ASTM D2596, kgf:	
Load Wear Index	27
Weld Point	≥160 ^{LMS}

Bomb Oxidation, ASTM D942, N/mm ² drop:	
100 hours	0.007
500 hours	0.12
Wheel Bearing Leakage, ASTM D4290, g	2.7
Infrared Spectroscopy	To match standard ^{LMS}
Flash Point - See SDS	

Compatibility with Polyalphaolefins

Since plastics and elastomers can be formulated and manufactured to have a wide range of physical properties, it is recommended that compatibility for the particular grade or product formulation be established for the specific application.

The following information details various materials and their compatibility with LOCTITE® LB 8632.

Compatibility of Various Materials with Polyalphaolefin Lubricants:

<u>Acceptable</u>	<u>Application Dependant</u>	<u>Not Recommended</u>
Fluorocarbon	Low Nitrile Buna N	High Nitrile Buna N
Fluorosilicone	Epichlorohydrin	Butyl
Polyurethane	Neoprene	Ethylene/Propylene
Silicone	Polysulfide	Buna S
Chlorinated Polyethylene	Chlorosulfonated Polyethylene	Polyisoprene
Propylene Oxide		
Polyacrylate		
Ethylene/Acrylic		

Compatibility with Fumed Silica

LOCTITE® LB 8632 utilizes fumed silica as a thickening agent. Other greases utilize various thickeners and not all of these are compatible with one another. When mixed together, typically incompatible thickening agents will decrease in viscosity and cause the grease to thin. When changing over greases it is important that you determine the compatibility of the thickeners involved to minimize the chance of damaging the lubrication site.

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

Loctite Material Specification^{LMS}

LMS dated September 24, 2004. Test reports for each batch are available for the indicated properties. LMS test reports include selected QC test parameters considered appropriate to specifications for customer use. Additionally, comprehensive controls are in place to assure product quality and consistency. Special customer specification requirements may be coordinated through Henkel Quality.

Storage

Store product in the unopened container in a dry location. Storage information may be indicated on the product container labeling.

Optimal Storage: 10 °C to 30 °C. Storage below 10 °C or greater than 30 °C can adversely affect product properties.

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Technical Service Center or Customer Service Representative.

Conversions

$(^{\circ}\text{C} \times 1.8) + 32 = ^{\circ}\text{F}$
 $\text{kV/mm} \times 25.4 = \text{V/mil}$
 $\text{mm} / 25.4 = \text{inches}$
 $\mu\text{m} / 25.4 = \text{mil}$
 $\text{N} \times 0.225 = \text{lb}$
 $\text{N/mm} \times 5.71 = \text{lb/in}$
 $\text{N/mm}^2 \times 145 = \text{psi}$
 $\text{MPa} \times 145 = \text{psi}$
 $\text{N}\cdot\text{m} \times 8.851 = \text{lb}\cdot\text{in}$
 $\text{N}\cdot\text{m} \times 0.738 = \text{lb}\cdot\text{ft}$
 $\text{N}\cdot\text{mm} \times 0.142 = \text{oz}\cdot\text{in}$
 $\text{mPa}\cdot\text{s} = \text{cP}$

Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes

and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 1.2