

Plicord® ExtremeFlex™ Petroleum Transfer



An extremely flexible and lightweight drop hose for use in tank truck and in-plant operation to transfer diesel, ethanol, gasoline, oil and petroleum base products up to 60% aromatic content. Corrugated construction for lower drag coefficient and superior abrasion resistance.

- Black Chemivic™ synthetic (corrugated) cover
- Temp Range: -40°F to 200°F (-40°C to 93°C)
- 200 PSI

Order #	Hose ID	Reel	Sale Price
GDY20459043	1"	100 Ft.	\$7.25 ft
GDY20459044	1-1/2"	100 Ft.	\$7.88 ft
GDY20459045	2"	100 Ft.	\$9.40 ft
GDY20459046	2-1/2"	100 Ft.	\$11.85 ft
GDY20459047	3"	100 Ft.	\$13.53 ft
GDY20459048	4"	100 Ft.	\$17.22 ft

Heavy Duty + Hot Water Premium Rubber Hose

A premium hot water hose. Rates to temperatures of -40°F to 190°F (-40°C to 88°C)



- Abrasion resistant
- Flexible in cold weather
- Internal spring coil prevents kinking at faucet
- Crush resistant brass fittings – M x F Brass 5/8" NPT

Order #	Size	Sale Price
GDY20582672	5/8" x 50 Ft.	\$30.80

FORTRESS® 1000 with Microban® Product Protection



For use on pressure washer machines with working pressures up to 1000 psi. Applications include wash-down service in food processing plants, dairies, packing houses, bottling plants, breweries, canneries and creameries. Its super abrasion and oil-resistant cover provides maximum protection against the adverse effects of oil and animal fats.

- Microban antimicrobial product protection inhibits the growth of bacteria, mold and fungi that can cause odor, stains or degradation of the hose cover
- Carbryn™ synthetic rubber, RMA Class A (High Oil Resistance) with Microban product protection
- Temperature Range: -20°F to 200°F (-29°C to 93°C)

Order #	Hose ID	PSI	Reel	Sale Price
GDY20141359	1/2"	1,000	500 Ft.	\$2.52 ft

Up to 2" Hose Assemblies Made While You Wait!



Crimped Jackhammer™ Hose



Designed for air tool applications on construction sites. Rates to temperatures of -65°F to 180°F (-54°C to 82°C).

- EPDM synthetic rubber RMA Class C (limited oil resistance)
- Red color
- 4-Spiral textile layer construction

Order #	Size	Sale Price
GDY20665753	3/4" x 50 Ft.	\$34.42

Extended Life™ XR16SC Abrasion Resistance Hose



X-LIFE™ XR16SC is for high-pressure service with tight bends needing abrasion resistance and flexibility. It is made for use with petroleum- and water-based hydraulic fluids. This hose has excellent impulse performance and flexibility, exceeding SAE 100R2 and SAE 100R16 standards.

- Temperature Range: -40°F to 212°F (-40°C to 100°C)
- Cover: Black synthetic rubber with extra abrasion, oil and weather resistance

Order #	Hose ID	Hose OD	PSI	Min. Bend Radius	Sale Price
GDY20693982	1/4"	0.54"	5,800	2.0"	\$2.86 ft
GDY20693983	3/8"	0.70"	5,000	2.5"	\$3.24 ft
GDY20693984	1/2"	0.81"	5,000	3.5"	\$2.54 ft
GDY20693987	3/4"	1.10"	3,500	5.0"	\$6.01 ft
GDY20693988	1"	1.40"	3,000	6.0"	\$7.66 ft

Spiraflex® Red Medium Duty



For medium-duty discharge applications in mining, construction, industry, agriculture and marine service. Limited oil and chemical application.

- Temperature Range: -10°F to 150°F (-23°C to 66°C)
- Cover: Red Pliovic, MSHA 2G-14C/16

Order #	Hose ID	Hose OD	PSI	Sale Price
GDY20012500	1-1/2"	1.71	150	\$1.26 ft
GDY20012501	2"	2.24	150	\$1.40 ft
GDY20012502	2-1/2"	2.79	150	\$2.09 ft
GDY20012503	3"	3.29	125	\$2.52 ft
GDY20012504	4"	4.32	100	\$4.11 ft
GDY20012505	6"	6.40	100	\$7.41 ft